


PL-TR-94-2247

DIELECTRIC PROPERTIES OF MAGNETOPLASMAS

Francis S. Johnson

**University of Texas/Dallas
Box 830688
Richardson, TX 75083-0688**

20 November 1989



Scientific Report No. 3

19950421 052


APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED



**PHILLIPS LABORATORY
Directorate of Geophysics
AIR FORCE MATERIEL COMMAND
HANSCOM AIR FORCE BASE, MA 01731-3010**

DATA CLASS 1 EXTENDED 8


"This technical report has been reviewed and is approved for publication"


(Signature)

David N. Anderson
Contract Manager


(Signature)

David N. Anderson
Branch Chief


(Signature)

William K. Vickery
Division Director

This report has been reviewed by the ESC Public Affairs Office (PA) and is releasable to the National Technical Information Service (NTIS).

Qualified requestors may obtain additional copies from the Defense Technical Information Center (DTIC). All others should apply to the National Technical Information Service (NTIS).

If your address has changed, if you wish to be removed from the mailing list, or if the addressee is no longer employed by your organization, please notify PL/TSI, 29 Randolph Road, Hanscom AFB, MA 01731-3010. This will assist us in maintaining a current mailing list.

Do not return copies of this report unless contractual obligations or notices on a specific document requires that it be returned.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188


Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 20 November 1989	3. REPORT TYPE AND DATES COVERED Scientific No. 3
4. TITLE AND SUBTITLE Dielectric Properties of Magnetoplasmas			5. FUNDING NUMBERS PE 61102F PR 2310 TA GL WU AA
6. AUTHOR(S) Francis S. Johnson			Contract F19628-93-K-0008
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Texas/Dallas Box 830688 Richardson, TX 75083-0688			8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Phillips Laboratory 29 Randolph Road Hanscom AFB, MA 01731-3010 Contract Manager: David Anderson/GPIM			10. SPONSORING/MONITORING AGENCY REPORT NUMBER PL-TR-94-2247
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) This report discusses the dielectric properties of magnetoplasmas by first considering a plasma at rest and then causing acceleration by increasing the electric field, E, slowly. The polarization current is calculated, then gravity is added which causes a current to flow. It is found that under the $J \times B$ force, the plasma stops in time and then reverses its direction of flow. Finally, the study considers an alternate treatment which does not involve dielectric properties.			
14. SUBJECT TERMS Dielectric properties Magnetoplasmas Electromagnetic forces			15. NUMBER OF PAGES 8
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT SAR

DIELECTRIC PROPERTIES OF MAGNETOPLASMAS

(dielectric, 11/20/89)

Consider a slab of plasma bounded by capacitor plates and permeated by a uniform, constant, magnetic field in the z direction. Apply a potential



⊙ B

difference across the plates so that E is in the +y direction. Then the plasma drift is in the +x direction and $v_x = E/B$. This agrees with the first term of Schmidt's equation (2-166),

$$v_p = \frac{E \times B}{B^2} + \frac{m \dot{E}_p}{q B^2}.$$

The second term is in the +y direction if E is increasing with time. Schmidt identifies this term as the polarization drift and notes that it is associated with the conversion of electric field energy to plasma kinetic energy; thus the polarization current is in the direction of E, and $J_p \cdot E > 0$ for $\dot{E} > 0$.

If we consider the plasma to be initially at rest (and cold) and accelerate it by increasing E slowly, how much electrical energy must be supplied to the capacitor to do this? When the electric field reaches the value E, the energy of the system is

$$\frac{\epsilon_0 E^2}{2} + \frac{Nm v^2}{2}.$$

The y component of motion of the guiding center is given by the second term in Schmidt's equation, and the displacement of the guiding center is

$$\int \frac{m}{q B^2} \frac{dE}{dt} dt = \frac{m E}{q B^2}.$$

The energy extracted from the electric field is

$$\int N q E \frac{m}{q B^2} \frac{dE}{dt} dt = \frac{Nm E^2}{2 B^2} = \frac{Nm v^2}{2},$$

which is just the kinetic energy imparted to the plasma.

The polarization current is

$$N q \frac{m}{q B^2} \frac{dE}{dt} = \frac{Nm}{B^2} \frac{dE}{dt}.$$

In dielectric terms, this contributes to the polarization P of the medium,

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

where

$$P = \frac{NmE}{B^2} = \frac{Nm}{\epsilon_0 B^2} \epsilon_0 E.$$

Thus the electrical susceptibility is

$$\chi_e = \frac{Nm}{\epsilon_0 B^2} = \frac{Nm v^2}{\epsilon_0 E^2}$$

and the relative permittivity is

$$\epsilon_r = 1 + \frac{Nm v^2}{\epsilon_0 E^2}.$$

The electric field energy density, expressed in terms of the dielectric properties, is

$$\frac{\epsilon_0 \epsilon_r E^2}{2} = \frac{\epsilon_0 E^2}{2} + \frac{Nm v^2}{2},$$

just the total energy mentioned above. The kinetic energy in the medium is recovered as electrical energy when the capacitor is discharged.

It is useful to look at the magnitude of some parameters typical of space plasmas:

$B = 10 \text{ nT} = 10^{-8} \text{ T}$	$N = 10^7 \text{ m}^{-3}$
$m = 1.67 \times 10^{-27} \text{ kg}$	$q = 1.6 \times 10^{-19} \text{ C}$
$\epsilon_0 = 8.85 \times 10^{-12}$	$v = 10^5 \text{ m/s}$
$E = Bv = 10^{-3} \text{ V/m}$	$\epsilon_r = 1.9 \times 10^7$
$P = \chi_e \epsilon_0 E = 1.68 \times 10^{-7} = Nq \Delta y; \quad \Delta y = 1.05 \times 10^5 \text{ m}$	
Proton gyro radius $= mv/qB = 1 \times 10^3 \text{ m}$ (smaller if thermal velocity is used).	

Thus the displacement due to polarization is of the order of 100 gyro radii or more. The charge density that must be applied to the capacitor plates to produce a velocity of 10^5 m/s is

$$\sigma_f = \epsilon_0 \epsilon_r E = 1.68 \times 10^{-7} \text{ C/m}^2;$$

this would produce a field of $1.9 \times 10^4 \text{ V/m}$ except for the polarization of the plasma. This also shows that $\epsilon_0 E^2/2$ is generally negligible by comparison with $Nmv^2/2$, the importance of the electric field in the problem notwithstanding.

Remove the Capacitor Plates

If a slab of plasma is moving through a uniform B field with velocity v , there must be surface charges sufficient to produce an electric field within the plasma that corresponds to its drift velocity. These surface charges are usually attributed to $\mathbf{v} \times \mathbf{B}$ forces. It seems natural enough to call this polarization of the medium, but this inevitably leads to confusion with the polarization current discussed above, which is in the opposite direction. To avoid this confusion, we will refer to the surface charge density as the induced


surface charge density σ_i , whose magnitude is the same as the free charge density that had to be placed on the capacitor plates in the previous discussion. Note that σ_i is positive on the lower surface and negative on the upper, whereas the surface charge density σ_p associated with the polarization is negative on the lower surface and positive on the upper, so the two tend to cancel.

$$\begin{aligned}\sigma_i &= \epsilon_0 \epsilon_r E = (1 + \chi_e) \epsilon_0 E \\ \sigma_p &= \chi_e \epsilon_0 E\end{aligned}$$

Thus, for space plasmas, the two cancel to within about one part in 10^7 , but it is just this small difference between them that is responsible for the electric field within the plasma.

Now Add a Gravity Field

(1) Start with stationary plasma between capacitor plates, with the plates connected together so that there is no electric field. To this add a gravity field



in the $+x$ direction; this will produce a current in the $-y$ direction, with

$$\mathbf{J} \times \mathbf{B} = -Nmg, \text{ or } \mathbf{J} = -Nmg/\mathbf{B}.$$

The current in the plasma produces a force on the plasma that cancels the force of gravity. The current is continuous but dissipationless, as the potential difference between the plates is zero.

(2) Now, remove the connection between the capacitor plates. Positive charge will accumulate on the lower plate, leading to the development of an E field in the $+y$ direction and consequent plasma drift in the $+x$ direction. There will also be a polarization current in the $+y$ direction, and it will almost cancel the current flow caused by the presence of gravity. We can consider the current flow due to gravity as all accumulating on the capacitor plates, with the force of gravity being totally cancelled by the current. But then we must recognize that there is a polarization current in the plasma that accelerates the plasma in the $+g$ direction, and that this acceleration is smaller than g by only about 1 part in 10^7 .

What must actually happen is that the two currents largely cancel one another, and the plasma is nearly in free fall. A very small part of the work done by the gravity field produces electric field energy $\epsilon_0 E^2/2$, and the predominant remainder goes into the production of kinetic energy.

(3) It is not necessary to imagine the presence of the capacitor plates at all. A slab of plasma in a uniform field B will accelerate at almost the rate g , while accumulating net charge density at its surface $\sigma = \sigma_i - \sigma_p$, electric field in the $+y$ direction $E = \sigma/\epsilon_0$, and electric field energy density $\epsilon_0 E^2/2$ in addition to its kinetic energy density.

For typical space plasmas, we noted that charges were displaced something like 100 km due to polarization. In the case of a plasma slab accelerated by gravity to 100 km/s, the net surface charge density is approximately σ_p/χ_e , and the charge displacements required to produce the electric field is only about 1 cm.

(4) Now let g act to slow down a slab of plasma that is initially moving with velocity v_0 in the $+x$ direction. From the preceding, the net surface



charge initially is $\sigma = \epsilon_0 E = \epsilon_0 B v_0$. This can be thought of in terms of $\sigma = \sigma_i - \sigma_p$, or $\sigma_i = \sigma + \sigma_p$, where $\sigma_p = P = \chi_e \epsilon_0 E$; i.e., $\sigma_i = \epsilon_0 E + \chi_e \epsilon_0 E = \epsilon_0 \epsilon_r E$. (This is just the charge that could be withdrawn from the capacitor plates in an earlier discussion.)

Now the g field causes a current to flow in the $+y$ direction, and the $J \times B$ force is in the $+x$ direction, again opposing gravity. Suppose for the sake of argument that it exactly cancels gravity. The current flow now acts to decrease the surface charge, and would reduce it to zero in a time

$$\sigma_i/J = \frac{\epsilon_r \epsilon_0 E}{Nmg/B}$$


(at which time the E field would be reduced to zero and the plasma would be stationary, but we must still show this).

The tendency of the current Nmg/B to decrease the surface charge is largely counteracted by the decreasing polarization of the medium. As the charge $\epsilon_0 \epsilon_r E$ is delivered to the upper boundary by the current that cancels the force of gravity on the plasma, the polarization charge on the upper surface is reduced from $\chi_e \epsilon_0 E$ to zero, and the depolarization current associated with this accelerates the plasma in the $-x$ direction, producing an acceleration almost equal to g . It is $\frac{\chi_e}{1+\chi_e} g$, where $\chi_e \approx 10^7$. The fact that the plasma does not slow down quite as fast as it would under action of gravity alone reflects the fact that electric field energy $\epsilon_0 E^2/2$ is eliminated in the process, contributing to the maintenance of velocity in the $+x$ direction.

Under action of the acceleration produced by the $J_p \times B$ force, the plasma stops in time $\frac{\epsilon_r \epsilon_0 EB}{Nmg}$, and then reverses its direction of flow and the direction of the electric field within it.

Alternate Treatment Not Involving Dielectric Properties

It is probably preferable to analyze the response of a slab of plasma to a gravitational field without invoking, or developing, the dielectric properties of the magnetoplasma. As before, consider a slab of plasma in the xz plane,



with gravity acting in the +x direction. Consider a current J in the +y direction; J will turn out to be negative so as to produce a $J \times B$ force on the plasma that opposes gravity. Later on, we will solve for J . Newton's Law gives for the acceleration of the plasma

$$Nma = Nmg + JB, \text{ or } a = g + JB/Nm.$$

The drift velocity must be consistent with the electric field that results from the surface charges produced by current J . The surface charge on the upper surface of the slab is

$$\sigma = \int J \, dt$$

and $E = -\sigma/\epsilon_0$ ($\epsilon_r = 1$, as no dielectric properties are involved in this analysis). For consistency, it is necessary that $v = E/B = \int a \, dt$, or that

$$-J/\epsilon_0 B = g + JB/Nm.$$

Therefore

$$-J = g \left(\frac{1}{\epsilon_0 B} + \frac{B}{Nm} \right) = \frac{Nmg}{B} \frac{1}{Nm v^2 / \epsilon_0 E^2 + 1},$$

and

$$a = -\frac{J}{\epsilon_0 B} = (Nmg/\epsilon_0 B^2) \frac{1}{Nm v^2 / \epsilon_0 E^2 + 1}$$

$$= g \, Nm v^2 \frac{1}{Nm v^2 + \epsilon_0 E^2}$$

$$= \frac{g}{1 + \epsilon_0 E^2 / Nm v^2}.$$

This is smaller than g by about 1 part in 10^7 . It is the same expression as $\frac{\chi_e}{1+\chi_e} g$ derived earlier making use of the dielectric properties of the plasma.